



Low Profile Air Table Actuator

The LPA actuator was developed for applications that require precise load guiding, with ultra-tight space constraints. This actuator minimizes thickness with a linear recirculating ball rail located next to the bore.

How to Order and List Prices

Model/Price	Dimensions mm (inch)
<p>LPA: Low Profile Air Table Actuator</p> <p>Part Number: LPA-8□-options</p> <p>Stroke Length: 10, 20, 30, 40, 50, 75mm</p> <p>List Price: 10, 20, 30 stroke: \$212.15 40, 50, 75 stroke: \$306.45</p> <p>Options: M (MRS position sensing for MS switch series): \$4.25 E (US customary-inch): N/C</p> <p>Availability: 5 working days</p>	

Stroke	A	B	C	E	F	G	K	L
10	25 (0.98)	4	24.7 (0.97)	49.7 (1.96)	50.2 (1.98)	58.6 (2.31)	27.7 (1.09)	25 (0.98)
20	25 (0.98)	4	34.7 (1.37)	59.7 (2.35)	60.2 (2.37)	68.6 (2.70)	34.7 (1.37)	25 (0.98)
30	24 (0.95)	6	44.8 (1.76)	69.7 (2.75)	70 (2.76)	78.4 (3.09)	44.8 (1.76)	48 (1.89)
40	26 (1.02)	6	64.7 (2.55)	89.7 (3.53)	90.2 (3.55)	98.6 (3.88)	64.7 (2.55)	52 (2.05)
50	43.1 (1.70)	6	77.5 (3.05)	102.5 (4.04)	103 (4.06)	111.4 (4.39)	77.5 (3.05)	86 (3.39)
75	45 (1.77)	6	105 (4.13)	130 (5.12)	130.5 (5.14)	138.9 (5.47)	105 (4.13)	90 (3.54)

For engineering specifications, refer to catalog FO, TBA-8 section, for basic operating parameters, materials of construction, loading, and accuracy.